



SPRGBW

RGBW Strip Kit

Features

Strip type	Flexible tape
IP rating	IP20
RGB / RGBW	RGBW
Bespoke lengths	No
Self-adhesive backing	Yes
Dimmable	Yes
LED/m	60
Input	220-240V 50/60Hz
LED lifetime	25,000h
CRI	80 Ra
SDCM	N/A

Installation information

Bathroom zone	N/A
Inrush current	75A 0.11ms
Construction material	Copper
Weight	19g per meter
Maximum ambient temperature	40°C
Electric class (1, 2, 3)	3

Photometrics @ 25°C

Product code	Reel length (m)	W	CCT	∠	lm	lm/W	Energy
SPRGBW	5	4.8W/m	White (4000K)	120°	373	78	
		4.8W/m	Red	120°	110	25	
		4.8W/m	Green	120°	296	62	
		4.8W/m	Blue	120°	79	18	

Wiring information

Cable / flying lead	Supplied with a minimum of 250mm fly lead with connector from one end
Type of wiring required	Parallel

Accessories

LED STRIP PROFILE RANGE	Profile range to house adhesive strip	Sold Separately	132
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately	465
LED COVE PACK	Coving to house adhesive strip	Sold Separately	133
PDCINTI-10V	1-10V dimming interface for use with 24V LED drivers	Sold Separately	456

Colour Change



RGBW



Ideal for accent lighting with 4.8W/m



Ideal for kitchen and bathroom with IP44

Guarantee

3 years


Features & benefits

Driver included


5m reel

Remote control included

Beam angle: 120°



5m/100mm



12mm