



collingwood

01604 495 151  
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

# BL03

Straight to mains Iroko wood

## Features

IK rating	N/A
IP rating	IP65
CSP Switchable	Fixed colour
LED Lifetime	70,000h L70
CRI	80 Ra
SDCM	3 SDCM

## Installation information

UK Bathroom Zone	-
Inrush Current	60A 0.037ms
Construction Material	Iroko wood
Weight	5500g
Maximum Ambient Temperature	35°C
SELV	N/A
Electric Class (1, 2, 3)	2

## Photometrics @ 25°C

Product code	Feature I	Feature II	Feature III	W	Colour	Beam	lm	lm/W	lx @ 1m
BL03FIS27	Triple LED	Chamfered	Side cable entry	5W	2700K	110°	156	31	78

## Wiring information

Cable / Flying Lead	NEW 1.5mm SY 2 Core PVC Steel Braid Cable. 2M Length.
Type of Wiring Required	Parallel

## LED driver

N/A (integrated SELV driver)	N/A	N/A	N/A	N/A	N/A	N/A
------------------------------	-----	-----	-----	-----	-----	-----

## Accessories

BOL LED BRACKET		Sold Separately
JB5	Gel filled junction box	Sold Separately

## Guarantee

7 year extended warranty

## Features & benefits

- 5W at 350mA or 700mA
- Coastal Protected
- IP65 ideal for outdoor areas
- Choice of wood finishes: Iroko, Sapele or Oak
- Pointed, Chamfered or Domed top
- Choice of low-voltage or straight-to-mains
- Side-entry cable or base-entry cable options
- Three colour temperature options: 2700K, 3000K or 4000K
- 7 year warranty

Light source energy efficiency:

Beam angle: 110°

