Wall lights specification sheet



WL012

IP54, 610lm straight to mains wall light

Features

| IK rating | IK04 | |
|-----------------|--------------|--|
| IP rating | IP54 | |
| CSP Switchable | Fixed colour | |
| Dimmable Option | No | |
| LED Lifetime | 30,000h L70 | |
| CRI | 80 Ra | |
| SDCM | 5 SDCM | |
| | | |

Photometrics @ 25°C

| Product code | Finish | w | Colour | Beam | lm | llm/W | lx @ 1m |
|--------------|---------------|-------|--------|------|-----|-------|---------|
| WL012X30 | Black RAL9011 | 11.0W | 3000K | 338° | 610 | 55 | 72 |
| WL012G30 | Grey RAL7022 | 11.0W | 3000K | 338° | 610 | 55 | 72 |

Accessories

No accessories required

Installation informa

| Inrush Current | 20A 0.5ms |
|--------------------------------|-------------------------|
| Construction Material | Powder coated aluminium |
| Weight | 1kg |
| Maximum Ambient Temperature | 40°C |
| Electric Class (1, 2, 3) | 1 |
| | |



| | 5 year extended guarantee avail |
|---------------|-------------------------------------|
| ation | Features & benefits |
| 20A 0.5ms | 11W |
| Powder coated | Intogral bracket for easy installed |

Integral bracket for easy installation IP54 ideal for framing doorways and entrances

Straight to mains screw terminals

Durable powder coated aluminium in contemporary black or grey finish

Provides a good light level for safe navigation at night

Wide light distribution with 360° beam angle



01604 495 151

Guarantee

0 0

in

collingwoodlighting.com

collingwoodled

/collingwoodlighting

collingwoodlighting

extended guarantee available

Beam angle: 338°



