



Black
WL014X

Grey
WL014G

WL014

IP54, 350lm cone up-down wall light

Features

IK rating	IK04
IP rating	IP54
CSP Switchable	Fixed colour
Dimmable Option	No
LED Lifetime	30,000h L70
CRI	80 Ra
SDCM	6 SDCM

Installation information

Inrush Current	20A 0.5ms
Construction Material	Powder coated aluminium
Weight	750g
Maximum Ambient Temperature	40°C
Electric Class (1, 2, 3)	1

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
WL014X30	Black RAL9011	5.7W	3000K	22°/26°	350	61	1061
WL014G30	Grey RAL7022	5.7W	3000K	22°/26°	350	61	1061

Accessories

No accessories required



collingwood

01604 495 151
collingwoodlighting.com

collingwoodled

/collingwoodlighting

collingwoodlighting

Guarantee

5 year extended guarantee available

Features & benefits

11W

Integral bracket for easy installation

IP54 ideal for framing doorways and entrances

Straight to mains screw terminals

Durable powder coated aluminium in contemporary black or grey finish

Narrow upper beam and wide lower beam provides both decorative and functional light

Provides a good amount of light for safe navigation at night

Integral bracket for easy installation

