

Wall lights specification sheet



WL015

IP65, 1,000lm up-down wall light

Features

IK rating	IK04
IP rating	IP65
CSP Switchable	Fixed colour
Dimmable Option	No
LED Lifetime	30,000h L70
CRI	80 Ra
SDCM	4 SDCM

Installation information

Inrush Current	20A 0.5ms
Construction Material	Powder coated aluminium
Weight	800g
Maximum Ambient Temperature	40°C
Electric Class (1, 2, 3)	1

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
WL015X30	Black RAL9011	13.0W	3000K	88°	1000	77	362
WL015G30	Grey RAL7022	13.0W	3000K	88°	1000	77	362

Accessories

No accessories required



collingwood

01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

5 year extended guarantee available

Features & benefits

- 13W
- Integral bracket for easy installation
- IP65 ideal for outdoor environments
- Ideal for columns and entrances
- Straight to mains screw terminals
- Durable powder coated aluminium in contemporary black or grey finish
- Up & down light for creating a feature of perimeters and entrances
- Up to 1000lm, makes this an ideal choice for columns and tall surfaces

Beam angle: 88°

