# Collingwood Lighting specification sheet



# CCDRV100RF

100W RF Driver

## **Features**

IP Rating	IP20
Dimmable Option	Yes
Driver Rated Wattage	100W

# Installation information

UK Bathroom Zone	1
Inrush Current	COLD START Max. 50A at 230VAC
Ambient Temperature Range	-25°C - 40°C
SELV	Yes
Electric Class (1, 2, 3)	2

#### **Accessories**

CCREMOTEB	Handheld remote control	Sold Separately
CCRFCONVWIFI	Colour Change RF-WIFI Wall Covertor, 12VDC	Sold Separately
CR575RGBW	5-Core PVC Cable	Sold Separately
LEDRGBWEXT	Colour Change 5-core extension lead for RGBW products	Sold Separately

## **PRODUCT CODES**

	Colour / Finish	Description
CCDRV100RF	White	Colour Change CV Driver, 24V 100W, RF 4CH



01604 495 151 collingwoodlighting.com

collingwoodled

/collingwoodlighting

in collingwoodlighting

#### Guarantee

5 years

## Features & benefits

All-in-one Driver for RGBW/RGB Systems

24v DC Output

Receives RF signal

4 channel 24V DC Constant Voltage Output

Multiple control inputs

Max. 4.16A/CH, CH1+CH2+CH3+CH4=4.16A

Power repeaters (PR3002) are required for RF installations with multiple zones that want to colour cycle. Requires driver.

