

Colour Change



RGBW



Ideal for accent lighting with low wattage



IP20 ideal for living room and hallways

Guarantee

3 years

Features & benefits

Cut point every 100mm

Hard-wearing clear covering

Foil backed flexible PCB dissipates heat (improves LED life and colour stability)


50 LEDs per meter in White and RGBW for an even spread of light

3M self-adhesive backing


Supplied in customised lengths (0.1m up to 4.9m in 100mm increments) 5m reel also available

Compatible with a large range of controllers

Beam angle: 120°



5m/100mm



LSR05

Colour change, self-adhesive flexible strip (15W max.)

Features

Strip type	Flexible tape
IP rating	IP20
RGB / RGBW	RGBW
Bespoke lengths	Yes
Self-adhesive backing	Yes
Dimmable	Driver dependent
LED/m	50
Input	24V DC
LED lifetime	50,000h
CRI	80 Ra
SDCM	N/A

Bathroom zone	N/A
Construction material	Flexible tape
Weight	20g per meter
Electric class (1, 2, 3)	3

Photometrics @ 25°C

Product code	Reel length (m)	W	CCT	∠	lm	lm/W	Energy
LSR0527050	5	5W/m	White (2700K)	120°	350	70	
		3.9W/m	Red	120°	130	33	
		3W/m	Green	120°	270	90	
		2.9W/m	Blue	120°	65	22	
LSR0530050	5	5W/m	White (3000K)	120°	350	70	
		3.9W/m	Red	120°	130	33	
		3W/m	Green	120°	270	90	
		2.9W/m	Blue	120°	65	22	
LSR0540050	5	5W/m	White (4000K)	120°	350	70	
		3.9W/m	Red	120°	130	33	
		3W/m	Green	120°	270	90	
		2.9W/m	Blue	120°	65	22	

Wiring information

Cable / flying lead	0.2m 5-core ribbon cable
Type of wiring required	Parallel

Control & LED drivers

See pages 424-425 for complete control and LED driver offer

Accessories

LED STRIP PROFILE RANGE	Profile range to house adhesive strip	Sold Separately	132
CF505RGBW	5-core RGBW ribbon cable	Sold Separately	427